

GIGA X3c

A high-performance move into the top class



Benefits

- 4.3" touchscreen colour display
- Precision ceramic disc grinder with Automatic Grinder Adjustment (A.G.A.®)
- Speed function thanks to additional hot water bypass
- 2 thermoblocks and 2 pumps

Recommended accessories

- Glass Cup Warmer
- Cool Control
- Milk Cooler Piccolo
- Smart Payment Box
- Coffee grounds disposal/ drip drain set
- Coffee to Go furniture range

Areas of use

Office floor solutions
 Seminar/conference facilities
 Breakfast room
 Catering
 Coffee to Go

Recommended maximum daily output
 150 cups

The GIGA X3c allows JURA to impressively demonstrate Swiss innovation and professionalism down to the very last detail. Anywhere where a capacity of up to 150 cups is the order of business, the machine impresses users with its quality, functionality and reliability. Coupled with top performance in every respect, this results in a high-tech automatic coffee machine that is ideally tailored to the requirements of large offices, the breakfast, seminar and conference venue sectors as well as self-service areas.



GIGA X3c

Technical data

Specific advantages

| | |
|---|-----------|
| No. of individually programmable specialties | 32 |
| One-Touch function | ■ |
| Automatic Grinder Adjustment (A.G.A.®) | ■ |
| Speed function | ■ |
| Automatic switchover from milk to milk foam | ■ |
| Compatible with J.O.E.® | ■ |
| Rotary Switch | ■ |
| Wireless ready | ■ |
| Smart Connect supplied as standard | ■ |
| Power hot water system (3 temperature levels) | 0.5l/min. |
| Recognition for second, ground coffee | ■ |
| Generating code groups | ■ |
| Active bean monitoring | ■ |
| Monitored drip tray | ■ |
| Aroma preservation cover | ■ |
| Swiss made | ■ |

JURA standards

| | |
|---|--|
| Pulse Extraction Process (P.E.P.®) | ■ |
| Variable VC brewing unit, from 5 g to 16 g | ■ |
| Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) | ■ |
| Grinder | Electrically adjustable ceramic disc grinder |
| High-performance pump, 15 bar | 2 |
| Thermoblock heating system | 2 |
| Fluid systems | 2 |
| JURA fine foam technology | ■ |
| Milk system | HP3 |
| Maintenance status display | ■ |
| Integrated rinsing, cleaning and descaling programme | ■ |
| Integrated milk system rinsing and cleaning programme | ■ |
| JURA hygiene: TÜV-certified | ■ |
| CLARIS filter cartridge | JURA water filter system |
| Energy Save Mode (E.S.M.®) | ■ |
| Zero-Energy Switch or power switch | ■ |

Settings and programming options

| | |
|--|----------|
| Programmable and individually adjustable amount of water | ■ |
| Programmable and individually adjustable coffee strength | 10 steps |
| Programmable milk/milk foam temperature | 10 steps |
| Store, copy and personalise products | ■ |
| Programmable brewing temperature | 3 steps |
| Programmable amount of milk/milk foam | ■ |
| Programmable temperature of hot water | 3 steps |
| Resettable day counter | ■ |
| Programmable switch-on/switch-off time | ■ |
| Shows the number of preparations for each individual product | ■ |

Design and materials

| | |
|--------------------------------|--------------------------------|
| Alu Frame Design® 3 mm | ■ |
| Display | TFT touchscreen colour display |
| Amber/white cup illumination | ■ |
| Powder chute for ground coffee | ■ |
| Sound design | ■ |

In figures

| | |
|-------------------------------------|---------------------|
| Height-adjustable dual spout | 70 – 159 mm |
| Height-adjustable hot-water spout | 69 – 165 mm |
| Bean container holding capacity | 1kg |
| Coffee grounds container (servings) | max. 40 |
| Cable length | approx. 1.1m |
| Voltage/Power | 220 – 240~ / 2300W |
| Current | 10A |
| Permanent water connection | G 3/4" |
| Stand-by power | < 0.5 W |
| Weight | 19 kg |
| Dimensions (W×H×D) | 32 × 56.5 × 49.7 cm |
| Article number/colour | 15230 Aluminium |
| EAN code | 7610917152308 |



Hygiene standards



www.tuv.com
ID 0000027526